CAMERA

Camera = "Virtual eye on site"
in conjunction with measurement
data:

- Creates trust and visually illustrates measurement data
- Recommended combination especially in conjunction with ice warning systems to limit patrols to the greatest possible extent
- Images of road condition day and night in real time with infrared spotlight (option) and GPRS transmission

- FixDome camera for flexible mounting, for interior and exterior use (IP65)
- 3MEGA resolution (QXGA, 2048x1536 pixels)
- Interchangeable lens from super wide-angle (90°) to telephoto (15°)
- Color sensor: 1 lux at 1/60 s, 0.05 lux at 1 s exposure time
- Stainless steel ring (polished, matt, powder-coated) and dome
- Outdoor wall bracket (IP65)

Technical Data	Order No.
Night vision camera	9983.00
Operating conditions	
Protection class	IP65
Resolution	2048x1536 pixels
Lens	From super wide-angle to telephoto
Color sensor	1 lux at 1/60 s, 0.05 lux at 1 s exposure time

Accessories	Order No.
Infrared spotlight LED	9984.00

Super wide-angle to telephoto lens
Resolution: 2048x1536 pixels
Color sensor: 1 lux at 1/60 s,
0.05 lux at 1 s exposure time

es&s AUSTRALIAN DISTRIBUTOR
Environmental Systems & Services | 8 River Street, Richmond VIC 3121 Australia |
T + 61 3 8420 8999 | F + 61 3 8420 8900 | environmental@esands.com | www.esands.com