

# Dipmeter

WATER LEVEL INDICATOR

## FEATURES

- Occupational Health and Safety brake
- Brake stops rapid descent
- Prevents reverse and forward tangling
- Stretch resistant survey tape
- Tape marked in m, cm, mm
- Clear polyethylene coating on tape
- Corrosion resistant construction
- Sensitivity control test button
- Visible and audible indicators
- 10mm diameter probe
- Replaceable 9V battery
- Mount and feeder to prevent wear and tear



DIPMETER



geotechnical  
solutions



The Water Level Indicator consists of a stainless steel probe attached to a flat steel survey tape. The conductors are stainless steel and the tape/conductor assembly is encapsulated in a tough, clear plastic coating. The tape and indicator unit are fitted with high grade bearings for ease of operation. The reel is supplied with a roller guide to protect the tape from damage at the top of the standpipe.

In operation, the probe is lowered down the open bore until it comes into contact with the water surface. This completes the circuit and activates an alarm. The operator then reads the depth of the probe off the tape at the collar. The new slimline stainless steel probe features an immersion well to eliminate false readings.

**es&s**  
www.esands.com

Environmental Systems & Services | 8 River Street, Richmond VIC 3121 Australia | T + 61 3 8420 8999 | F + 61 3 8420 8900 | geotechnical@esands.com |

## TECHNICAL SPECIFICATIONS

<b>Tape</b>	Steel, yellow enamelled, marked in red (m) and black (cm, mm)
<b>Conductors</b>	Stainless Steel
<b>Coating</b>	Clear polyethylene
<b>Probe Dimensions</b>	10mm diameter x 150mm long with stainless steel counterweights
<b>Weight</b>	11kg
<b>Probe Materials</b>	Stainless Steel, teflon
<b>Cable Reel Dimensions</b>	430 x 370 x 270mm
<b>Cable Reel Construction</b>	Epoxy coated steel
<b>Ranges Available</b>	100m, 200, 250m
<b>Alarm Function</b>	9V Battery Operated
<b>Accessories</b>	Roller guide, carry bag

