

## Water Level Indicators

### Series BFK

Water level indicator with PVC rounded cable, four-conductors, with kevlar core and external protection sheath (diam. 4.7 mm).

- Graduation at 1 centimetre intervals (directly printed on the cable itself and protected by external anti-scratching transparent polihuretane)
  - Probe diameter: 10 mm
  - Water level indication by both acoustic signal and led
  - Downhole indicator available on request
  - Available lengths:
 

30m	(Cod.FRE-019-000)
50m	(Cod.FRE-020-000)
100m	(Cod.FRE-021-000)
150m	(Cod.FRE-022-000)
200m	(Cod.FRE-023-000)
300m	(Cod.FRE-024-000)
400m	(Cod.FRE-025-000)
500m	(Cod.FRE-026-000)
- (longer lengths available on request)



#### Available Models

- Series BFK
- Series BFKT
- Series BFP
- Series BFM

### Series BFKT

Water level indicator with PVC rounded cable, four-conductors, with kevlar core and external protection sheath (diam. 4.7 mm).

- Graduation at 1 centimetre intervals (directly printed on the cable itself and protected by external anti-scratching transparent polihuretane)
  - Probe diameter: 10 mm
  - Water level indication by both acoustic signal and led
  - Temperature display
  - Temperature sensor (accuracy  $\pm 0.1^{\circ}\text{C}$ , range from  $-10$  to  $+70^{\circ}\text{C}$ )
  - Available lengths:
 

30m	(Cod.FRE-029-000)
50m	(Cod.FRE-030-000)
100m	(Cod.FRE-031-000)
150m	(Cod.FRE-032-000)
200m	(Cod.FRE-033-000)
300m	(Cod.FRE-034-000)
400m	(Cod.FRE-035-000)
- (longer lengths available on request)



#### Available accessories

Downhole indicator (for Mod.BFK only)

Hook for water sampler (bailer)

Customized aluminium reels

## Series BFP

Water level indicator with flat two-conductors cable (mm 2x10)

- Graduation at 1 centimetre intervals (silk-screen printing on cable itself)
- Probe diameter: 10 mm
- Water level indication by both acoustic signal and led
- Available lengths:

20m	(Cod.FRE-010-000)
30m	(Cod.FRE-018-000)
50m	(Cod.FRE-011-000)
100m	(Cod.FRE-012-000)
150m	(Cod.FRE-013-000)
200m	(Cod.FRE-014-000)
300m	(Cod.FRE-015-000)
400m	(Cod.FRE-016-000)
500 m	(Cod.FRE-017-000)



# New

BFM cable with graduation  
at 1 mm intervals



## New Series BFM

Water level indicator with flat tape with a core spring steel with 2 copper wires coated with yellow nylon.

- **Graduation at 1 millimeter intervals**

Black millimetre graduation over total length, black centimetre and decimetre figures, metre figures in red repeated before each decimetre

- Probe diameter: 15 mm, made of refined steel with electrode and insulation
- Water level indication by both acoustic signal and led
- Available lengths:

20m	(Cod.FRE-060-000)
30m	(Cod.FRE-069-000)
50m	(Cod.FRE-061-000)
100m	(Cod.FRE-062-000)
150m	(Cod.FRE-063-000)
200m	(Cod.FRE-064-000)
300m	(Cod.FRE-065-000)
400m	(Cod.FRE-066-000)
500 m	(Cod.FRE-067-000)



### DISTRIBUTOR



## Available options for Water Level Indicators

- Hook for water sampler (bailer) : Mod. BFK, BFKT & BFP
- Downhole indicator : Mod.BFK only

## Water Level Indicator Reels

All these water level indicators are mounted on robust reels; reel dimensions may vary in relation to cable length and size: the reel is realised in shock resistant PVC with swing handle and brake; the frame in spray painted iron



Downhole indicator

- dimensions 25cm x 18cm x h35cm:  
for water level indicators with a cable length of 20 to 100m (Cod.FRE-042-000)
- dimensions 32cm x 22cm x h40cm:  
for water level indicators with a cable length of 150 to 200m
- dimensions 38cm x 25cm x h52cm:  
for water level indicators with a cable length of 300 to 700m

It is also possible to supply made to measure cable reels in aluminium (Serie "Professional").

## Bailers

These water samplers represent the ideal solution for water quality monitoring. Robust, handy and inexpensive, they are made in PVC to avoid sampler contamination. There are no mechanical parts in movement: a ball valve closes the sampler bottom as soon as it is released.

Dimensions: length 950mm, diameter 40mm. Cod.BAI-001-022.



Water Level indicator BFK  
"Professional"



Hook for water sampler (bailer)



Nylon cable 50 and 100 m long, non-graduated, with cable reel are also available (Cod.BAI-002-000); as an alternative we can also deliver measuring reinforced fibre-glass tapes 50 or 100m long (Cod.BAI-003-002 e BAI-004-002), with handle and hook for the bailer.

## DISTRIBUTOR

